

SV1430

DATA SHEET

| | |
|------------------------------|------------------------|
| POWER *: | 22.5 kW @3000 rpm |
| MAX. TORQUE: | 84.0 Nm @2000 rpm |
| NOISE LEVEL **:: | 72 dB(A) |
| WEIGHT ***: | 273 Kg |
| DIMENSIONS (WxLxH): | 71 x 90 x 83.5 cm |
| EMISSIONS COMPLIANCE: | 2004/26 CE Stage III A |
| FUEL CONSUMPTION: | 7,0 l/h |

* **POWER:** ISO 3046 IFN

** **NOISE:** taken at 7 meters @2800 rpm without load

*** **WEIGHT:** oil and cooling liquid included

Measured technical data (+/- 1%) may be subject to changes.



STANDARD EQUIPMENT

- Base incorporated 40 liters fuel tank
- SAE 5 - 6" 1/2 flanging
- Electric accelerator with step by step key
- Control panel with tachometer and hour counter
- 12 V electric start
- Exhaust silencer

OPTIONAL ACCESSORIES

- Hydraulic pump adapter on 1st PTO
- Cylindrical shaft extensions
- Industrial hand lever clutches
- 24 V electric start

Engine: Kohler KDW 1404
Cylinders: 4
Displacement: 1372 cm³



SV1430

- Bore (mm): 75
- Stroke (mm): 77.6
- Injection system: IDI
- Compression ratio: 22.8:1
- 4-stroke diesel engine with in-line cylinders
- Liquid cooled with axial fan
- Indirect injection with injector pump in head
- Single-shaft distribution in head
- Forced lubrication with vane pump on the crankshaft
- Water pump in the engine block
- Aluminum cylinder head
- Cast iron engine block with re-borable integral liners