UCI-FRAMGroup

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Holts Professional Brake Cleaner

Product Code: HMTN0101A, PRO25A
Product Use: Brake Parts Aerosol Spray

Restriction of Use: Refer to Section 15

New Zealand Supplier: UCI - Fram Group NZ Ltd

Address: 40 Firth St Drury

Auckland

Telephone: +64 9 2946752 Fax Number: +64 9 2946751

Emergency Telephone: 0800 764 766 (National Poison Centre)

Manufacturer: Holt Lloyd International

Address: Barton Dock Road

Manchester M32 OYQ England

Inquires +44 161 866 4800

Date of SDS Preparation: 28 March 2015

Section 2. Hazards Identification

This substance is hazardous according to the HSNO (Minimum Degrees of Hazard) Regulations 2001

EPA Approval No: Aerosols (Flammable) - HSR002515

Pictograms







Flammable

Irritant

Ecotoxic

Signal Word: DANGER

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
2.1.2A	H222	Extremely flammable aerosol.	Category 1
6.3A	H315	Causes skin irritation.	Category 2
6.4A	H319	Causes serious eye irritation.	Category 2A
9.1B	H411	Toxic to aquatic life with long lasting effects.	Category 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.

P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe mist, vapours, or spray.
P264	Wash exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P331	Do NOT induce vomiting.
P338	Remove contact lenses, if present and easy to do. Continue rinsing.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use CO ₂ , dry powder, chemical foam for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha Petroleum Hydrotreated Light	60-95	64742-49-0
Butane	5-10	106-97-8
Isobutane	1-5	75-28-5

Section 4: I not Ala Measures	Section 4.	First Aid Measures
-------------------------------	------------	--------------------

Routes of Exposure:

If in Eyes Make sure to remove any contact lenses from the eyes before rinsing.

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. If eye irritation persists: Get

medical advice.

If on Skin Wash with plenty of soap and water. Take off contaminated clothing and

wash before re-use. If skin irritation occurs: get medical advice/attention.

If Swallowed DO NOT induce vomiting. Never give anything to the mouth of an

unconscious person. Immediately call a POISON CENTER (0800 764 766)

or a doctor/physician.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if

breathing becomes difficult.

Section 5. Fire Fighting Measures

Hazard Type	Flammable Aerosol
Hazards from combustion products	Carbon monoxide, carbon dioxide.
Suitable Extinguishing media	Use CO ₂ , dry powder, or chemical foam for extinction. Always choose fire-extinguishing media appropriate for surrounding materials.
Precautions for firefighters and special protective clothing	Risk of exploding containers if heated. Keep water run-off out of sewers and water sources. Wear full protective gear.
HAZCHEM CODE	2WE

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Have fire extinguishers close at hand while attending the spill. Collect for reclamation or absorb in vermiculite, dry sand or similar material.

Do not contaminate water sources or sewer. Dispose of according to Local Regulations.

Section 7. Handling and Storage

Precautions for Handling:

- Read label before use.
- Keep away from heat/sparks/open flames/hot surfaces.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wash hands thoroughly after handling.
- Avoid release to the environment.
- Wear protective clothing.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- · Keep out of reach of children
- Store locked up.
- Store in a well-ventilated place. Keep cool.
- Store above freezing.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance ppm mg/m³ ppm mg/m³

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

Engineering Controls

Ensure adequate ventilation is available.

Personal Protection

Eyes	Wear goggles with side shields. Avoid wearing contact lenses.	
Hands and	Use suitable protective gloves and clothing if risk of skin contact. EN374	
Skin	Rubber gloves are recommended.	
Respiratory	If ventilation is poor, use appropriate cartridge respirator.	

Section 9 Physical and Chemical Properties

Appearance	Clear liquid spray
Odour	Solvent
Odour Threshold	Not applicable
рН	Not applicable
Boiling Point	Not applicable
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	Not available
Flammability	Highly Flammable
Upper and Lower Exposure	Not applicable
Limits	
Vapour Pressure	Not applicable
Vapour Density	Not applicable
Relative Density	Not applicable
Solubilities	Insoluble
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not applicable
Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Keep away from heat, sparks, open flames and hot surfaces
Incompatible Materials	Strong acids and alkalis. Oxidisers.
Hazardous Decomposition	Carbon monoxide, Carbon dioxide.
Products	

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	May be fatal if swallowed and enters airways.
Eye	Causes serious eye irritation.
Skin	Causes skin irritation.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive	Not applicable.
Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method:

Precautions: Dispose of waste according to Local regulations. Collected spillage and unused product must be placed in a sealable waste container for disposal through a disposal company. Ensure waste container is labelled "Hazardous Waste - Flammable, Ecotoxic"

Disposal methods to avoid: Do not allow product to enter sewers, streams, or waterways

Section 14 Transport Information

This product is classified as a Dangerous Good in NZ; NZS 5433:2012

Road and Rail Transport

UN No: 1950 Class-primary 2.1 Packing Group **PGII** Proper Shipping Name: **AEROSOLS**

Air Transport

UN No: 1950 Class-primary 2.1 Packing Group PGII Proper Shipping Name:

AEROSOLS

Marine Transport

UN No: 1950 Class-primary 2.1 Packing Group **PGII** Proper Shipping Name: **AEROSOLS**

Section 15 Regulatory Information

EPA Approval Code: Aerosols (Flammable) - HSR002515

HSNO Classification: 2.1.2A, 6.3A, 6.4A, 9.1B

HSNO Controls:

Trigger quantities for this substance:

	Trigger Quantity	
Approved Handler	3000L awc	
Location Certificate	3000L awc	
Tracking Trigger Quantities	Not required	
Signage Trigger Quantities	3000L awc	
Emergency Response Plan	1000L	
Secondary Containment	1000L	
Restriction of Use	None	

Section 16	Other Information
Glossary	
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms
	inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible
	authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit
AWC	Aggregate water capacity

1. HSNO Approved Code of Practice: Preparation of Safety Data Sheets, September 2006.

Disclaimer

This document has been issued by UCI Fram Ltd and serves as their Safety Data Sheet ('SDS'). It represents the appropriate safety and handling precautions for the product at the time of issue. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated., it does not provide any warranty as to accuracy or completeness. Please contact the country distributor, if further information is required.

Issue Date: 28 March 2015 Review Date: 28 March 2020