UCI-FRAMGroup

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Holts Professional Maintenance Spray

Product Code: HMTN0501A,

Product Use: Maintenance Aerosol Spray

Restriction of Use: Refer to Section 15

New Zealand Supplier: UCI - Fram Group NZ Ltd

Address: 40 Firth St Drury

Auckland

Telephone: +64 9 2946752 Fax Number: +64 9 2946751

Emergency Telephone: 0800 764 766 (National Poison Centre)

Manufacturer: Holt Lloyd International

Address: Barton Dock Road

Manchester M32 OYQ England

Inquires +44 161 866 4800

Date of SDS Preparation: 28 March 2015

Section 2. Hazards Identification

This substance is hazardous according to the HSNO (Minimum Degrees of Hazard) Regulations 2001

EPA Approval No: Aerosols (Flammable) - HSR002515

Pictograms







Flammable

Irritant

Aspiration

Signal Word: DANGER

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
2.1.2A	H222	Extremely flammable aerosol.	Category 1
6.1E(aspiration)	H304	May be fatal if swallowed and enters airways.	Category 1
6.3A	H315	Causes skin irritation.	Category 2
6.4A	H319	Causes serious eye irritation.	Category 2A
9.1B	H411	Toxic to aquatic life with long lasting effects.	Category 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe mist, vapours, or spray.
P264	Wash exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P331	Do NOT induce vomiting.
P338	Remove contact lenses, if present and easy to do. Continue rinsing.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use CO ₂ , dry powder, chemical foam for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha Petroleum	30-70	64742-49-0
Butane	10-35	106-97-8
Isobutane	5-10	75-28-5
Sulfonate de Calcium	1-15	90622-57-4
Distillates Petroleum	10-35	6472-46-7

Section 4.	First Aid Measures
------------	--------------------

Routes of Exposure:

If in Eyes Make sure to remove any contact lenses from the eyes before rinsing.

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. If eye irritation persists: Get

medical advice.

If on Skin Wash with plenty of soap and water. Take off contaminated clothing and

wash before re-use. If skin irritation occurs: get medical advice/attention.

If Swallowed DO NOT induce vomiting. Never give anything to the mouth of an

unconscious person. Immediately call a POISON CENTER (0800 764 766)

or a doctor/physician.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position

and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Section 5.	Fire Fighting Measures	
Section 5.	Fire Fighting Measures	

Hazard Type	Flammable Aerosol
Hazards from combustion products	Carbon monoxide, carbon dioxide.
Suitable Extinguishing media	Use CO ₂ , dry powder, or chemical foam for extinction. Always choose fire-extinguishing media appropriate for surrounding materials.
Precautions for firefighters and special protective clothing	Risk of exploding containers if heated. Keep water run-off out of sewers and water sources. Wear full protective gear.
HAZCHEM CODE	2WE

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Have fire extinguishers close at hand while attending the spill. Collect for reclamation or absorb in vermiculite, dry sand or similar material.

Do not contaminate water sources or sewer. Dispose of according to Local Regulations.

Section 7. Handling and Storage

Precautions for Handling:

- · Read label before use.
- Keep away from heat/sparks/open flames/hot surfaces.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wash hands thoroughly after handling.
- Avoid release to the environment.
- Wear protective clothing.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Keep out of reach of children
- Store locked up.
- Store in a well-ventilated place. Keep cool.
- Store above freezing.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

TWA STEL Substance ppm mg/m³ ppm mg/m³

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

Engineering Controls

Ensure adequate ventilation is available.

Personal Protection

Eyes	Wear goggles with side shields. Avoid wearing contact lenses.	
Hands and	Use suitable protective gloves and clothing if risk of skin contact. EN374	
Skin	Rubber gloves are recommended.	
Respiratory	If ventilation is poor, use appropriate cartridge respirator.	

Section 9 Physical and Chemical Properties

Appearance	Clear liquid spray
Odour	Solvent
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	Not applicable
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	Not available
Flammability	Highly Flammable
Upper and Lower Exposure	Not applicable
Limits	
Vapour Pressure	Not applicable
Vapour Density	Not applicable
Relative Density	Not applicable
Solubilities	Insoluble
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not applicable
Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.	
Conditions to Avoid	Keep away from heat, sparks, open flames and hot surfaces	
Incompatible Materials	Strong acids and alkalis. Oxidisers.	
Hazardous Decomposition	osition Carbon monoxide, Carbon dioxide.	
Products		

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.	
Dermal	Not applicable.	
Inhalation	May be fatal if swallowed and enters airways.	
Eye	Causes serious eye irritation.	
Skin	Causes skin irritation.	

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive	Not applicable.
Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	May be fatal if swallowed and enters airways.

STOT/SE	Not applicable.	
STOT/RE	Not applicable.	

Section 12. Ecotoxicological Information

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method:

Precautions: Dispose of waste according to Local regulations. Collected spillage and unused product must be placed in a sealable waste container for disposal through a disposal company. Ensure waste container is labelled "Hazardous Waste - Flammable, Ecotoxic"

Disposal methods to avoid: Do not allow product to enter sewers, streams, or waterways

Section 14 **Transport Information**

This product is classified as a Dangerous Good in NZ; NZS 5433:2012

Road and Rail Transport

UN No: 1950 Class-primary 2.1 Packing Group **PGII** Proper Shipping Name:

AEROSOLS

Air Transport

UN No: 1950 Class-primary 2.1 Packing Group **PGII** Proper Shipping Name: **AEROSOLS**

Marine Transport

UN No: 1950 Class-primary 2.1 Packing Group **PGII AEROSOLS** Proper Shipping Name:

Section 15 Regulatory Information

EPA Approval Code: Aerosols (Flammable) - HSR002515

HSNO Classification: 2.1.2A, 6.1E(aspiration), 6.3A, 6.4A, 9.1B

HSNO Controls:

Trigger quantities for this substance:

	Trigger Quantity
Approved Handler	3000L awc
Location Certificate	3000L awc
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	3000L awc

Emergency Response Plan	1000L
Secondary Containment	1000L
Restriction of Use	None

Section 16 Other Information

Glossary

EC₅₀ Median effective concentration. EEL Environmental Exposure Limit. EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms.

LC₅₀ Lethal concentration that will kill 50% of the test organisms

inhaling or ingesting it.

LD₅₀ Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level
WES Workplace Exposure Limit
AWC Aggregate water capacity

1. HSNO Approved Code of Practice: Preparation of Safety Data Sheets, September 2006.

Disclaimer

This document has been issued by UCI Fram Ltd and serves as their Safety Data Sheet ('SDS'). It represents the appropriate safety and handling precautions for the product at the time of issue. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated., it does not provide any warranty as to accuracy or completeness. Please contact the country distributor, if further information is required.

Issue Date: 28 March 2015 Review Date: 28 March 2020