

| Power Output Ratings |     | 50 Hz / 400 V |  |
|----------------------|-----|---------------|--|
| Standby Power (ESP)  | kVA | 200           |  |
|                      | kW  | 160           |  |
| Prime Power (PRP)    | kVA | 183           |  |
|                      | kW  | 146           |  |

| Standby Power (ESP)            |        |  |      |
|--------------------------------|--------|--|------|
| Manufacturer                   |        | PERKINS                                    |      |
| Model                          |        | 1106A-70TAG3                               |      |
| No of Cylinder / Configuration |        | 6 - INLINE                                 |      |
| Displacement                   | lt     | 7,01                                       |      |
| Bore / Stroke                  | mm     | 105 / 135                                  |      |
| Compression Ratio              |        | 16:1                                       |      |
| Aspiration                     |        | Turbocharged and Air-to-Air Charged Cooled |      |
| Governor Type                  |        | MECHANIC                                   |      |
| Cooling System                 |        | WATER                                      |      |
| Coolant Capacity               | lt     | 21   |      |
| Lubrication Oil Capacity       | lt     | 16,5                                       |      |
| Electrical System              | VDC    | 12   |      |
| Speed / Frequency              |        | 1500 rpm / 50 Hz                           |      |
| Engine Gross Power             | kWm    | 177  |      |
| Fuel Consumption               | lt/h   | 110 %                                      | 44   |
|                                |        | 100 %                                      | 41,2 |
|                                |        | 75 %                                       | 30,9 |
|                                |        | 50 %                                       | 20,6 |
| Exhaust Outlet Temperature     | °C     | 580  |      |
| Exhaust Gas Flow               | m³/min | TBA  |      |
| Combustion Air Flow            | m³/min | TBA  |      |
| Cooling Air Flow               | m³/min | TBA  |      |

| Alternator                         |     |  |
|------------------------------------|-----|--|
| Manufacturer                       |     | MARELLI                                      |
| Model                              |     | MJB250MB4                                    |
| No of Phase                        |     | 3  |
| Power Factor                       |     | 0,8  |
| No of Bearing                      |     | SINGLE                                       |
| No of Poles                        |     | 4  |
| No of Leads                        |     | 12   |
| Voltage Regulation ( Steady State) |     | ± %0,5                                       |
| Insulation Class                   |     | H  |
| Degree of Protection               |     | IP 23  |
| Excitation System                  |     | AVR (Automatic Voltage Regulator), Brushless |
| Connection Type                    |     | STAR   |
| Total Harmonic Content (No Load)   |     | < %2   |
| Frequency                          | Hz  | 50   |
| Voltage Output                     | VAC | 230 / 400                                    |
| Rated Power (Standby)              | kVA | 205  |
| Efficiency                         | %   | 93   |

|           | W x L x H (mm)     | Weight (kg) | Fuel Tank (lt) | Noise dB(A)<br>@ 1m |
|-----------|--------------------|-------------|----------------|---------------------|
| Canopied  | 1200 x 3860 x 1850 | 2280        | 330            | 76                  |
| Open Skid | 1200 x 2700 x 1470 | 1710        | 330            | TBA                 |





#### Standby Power

Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

#### Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.

- Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.

- All information given in this leaflet is intended for general use only. Due to a policy of continuous improvement we reserve the right to amend details and specifications without notice and all information given is subject to TransDiesel's current conditions of sale.

TBA: To Be Ask

TBD: To Be Determined

NA: Not Available

N/A: Not Applicable

TTD200PE5A0414-EN