

Tx Razor SAE 30 Engine Oil

Product code: TX-E0090/*

Description

Tx Razor SAE 30 Engine Oil is a monograde engine oil for high-output petrol and diesel engines operating under severe duty. It is formulated from top-quality high viscosity index, low pour point base stock, and advanced additives imparting superior detergency together with high dispersant, antioxidant, anti-corrosion, anti-wear and anti-foam properties.

Tx Razor SAE 30 Engine Oil is also recommended where an SAE 30 engine oil is required for transmission or hydraulic systems.

Performance characteristics

Superior detergency and dispersancy. Minimises the formation of lacquer, varnish, sludge and other engine deposits, and helps prevent ring sticking while promoting high piston-cleanliness.

Marked resistance to deterioration. Especially that caused by oxidation due to prolonged high-temperature operation.

Anti-wear. Protects parts against premature wear and failure.

Anti-corrosion. Metals surfaces are protected against moisture and acidic combustion by-products.

Anti-foam. Releases air quickly, preventing excessive foaming and cavitation.

Performance specifications

API CF/SH

Typical physical characteristics

Characteristic	Typical Result	Test Method
Appearance	Amber, clear & bright	Visual
Kinematic viscosity (cSt @ 100°C)	10.9	ASTM D445
Kinematic viscosity (cSt @ 40°C)	92.7	ASTM D445
Viscosity index	102	ASTM D2270
Density (kg/l @ 15°C)	0.89	ASTM 4052
Pour point (°C)	-18	ASTM D97
Flash point (COC, °C)	240	ASTM D92